

Humidity Sensor

HUM-21+ Series

FEATURES

- **Molded thermoset plastic housing with cover**
- **Linear voltage output vs %RH**
- **Laser trimmed interchangeability**
- **Low power design**
- **High accuracy**
- **Fast response time**
- **Stable, low drift performance**
- **Chemically resistant**

TYPICAL APPLICATIONS

- **Meteorology**
- **Drying/refrigeration**
- **Weather stations**
- **Battery-powered systems**

The HUM-21+ Series humidity sensor is designed specifically for high accuracy measurements. Direct input to datalogger EKO21 or iBOX (or other device) is made possible by this sensor's linear voltage output. With a typical current draw of only 200 μ A, the HUM-21 Series is ideally suited for low drain, battery operated systems. Tight sensor interchangeability reduces or eliminates OEM production calibration costs.

The HUM-21+ Series delivers **instrumentation-quality** RH (Relative Humidity) sensing performance in a low cost. The RH sensor is a laser trimmed thermoset polymer capacitive sensing element with on-chip integrated signal conditioning. The sensing element's multilayer and the hydrophobic filter provides excellent resistance to application hazards such as wetting, dust, dirt, oils, and common environmental chemicals and can be built in weather screen WS21 for **outdoor applications** (for protection against rain and solar radiation), can be supplied also together with temperature sensor TS21: **a low cost precision and compact Temperature/ Humidity sensor unit!**



WS21 weather screen

PERFORMANCE SPECIFICATIONS

Parameter	Condition
<u>RH Accuracy</u>	typ. $\pm 2\%$ RH, 0-100% RH non-condensing, 25 °C, $V_{\text{supply}} = 5 \text{ Vdc}$
RH Linearity	$\pm 0.5\%$ RH typical